


Installation Example in asphalted areas Class E 600 - F 900



* y = Channel height plus camber

Category according to EN 1433 / DIN 19580		A 15	B 125	C 250	D 400**	E 600**	F 900**	Applying to following systems: FASERFIX KS 100, 150, 200
Foundation: width x / height y / thickness z (in cm)						15 / * / 20	15 / * / 20	
EN 206-1 / DIN 1045-2	quality of concrete stretcher					C30/37 XF4, XM1	C30/37 XF4, XM1	
	The named concrete quality is a minimum quality	without danger of frost on the lateral support				C25/30 X0	C25/30 X0	
	with danger of frost on the lateral support					C25/30 XF3	C25/30 XF3	
The installation examples / advise constantly are adapted to the technical conditions. With new editions older expenditures lose their validity. Before planning or installation please verify the current version at www.hauraton.com In building construction is a sealing layer below the channels necessary.					Date: 25.05.2023		Our general installation instructions apply.	
The installation example represents a proven recommendation from HAURATON. The final responsibility for the execution lies with the planner in charge. Specific conditions of the project must be taken into account.							Format DIN	A4
							scale	1:6
							EBBw	 Unit 4, Frenchs Avenue LU6 1BH Dunstable / Bedfordshire United Kingdom Tel. +44 1582 501380 TS-UK@hauraton.com
** Installation situations of drainage systems with high dynamic loads (e.g. airports, motorways and manoeuvring areas of buses, lorries and forklifts, etc.) are not sufficiently considered in DIN EN 1433. Please contact us for such applications to work out project-specific solutions.					0000120242_BRITISH.dwg		4	
					FF-KS-200 Typ 010 Rinnenunterteil Einbaubeispiel Klasse F 900 in Asphalt			